

KIPAS KRAFTLINER (KRF)

KK-TS-012 Rev.05

Date: 17.02.2025

TARGET CHARACTERISTICS

| SUBGRADE | GRAMMAGE | MOISTURE | SCT CD | SCT INDEX | BURST STRENGHT | BURST INDEX | COBB60 TOP |
|----------|------------------|----------|--------|-----------|----------------|-----------------------|------------------|
| KRF | g/m ² | % | kN/m | kN.m/kg | kPa | kPa.m ² /g | g/m ² |
| KRF 100 | 100 | 8,0 | 2,0 | 20 | 350 | 3,50 | 35 |
| KRF 115 | 115 | 8,0 | 2,3 | 20 | 402 | 3,50 | 35 |
| KRF 135 | 135 | 8,0 | 2,7 | 20 | 473 | 3,50 | 35 |
| KRF 150 | 150 | 8,0 | 3,0 | 20 | 525 | 3,50 | 35 |
| KRF 175 | 175 | 8,0 | 3,4 | 19,4 | 610 | 3,50 | 35 |
| KRF 185 | 185 | 8,0 | 3,6 | 19,4 | 645 | 3,50 | 35 |
| KRF 200 | 200 | 8,0 | 3,9 | 19,5 | 700 | 3,50 | 35 |
| KRF 275 | 275 | 8,0 | 4,9 | 17,8 | 880 | 3,20 | 35 |

GUARANTEED CHARACTERISTICS

| SUBGRADE | GRAMMAGE | MOISTURE | SCT CD | SCT INDEX | BURST STRENGHT | BURST INDEX | COBB60 TOP |
|----------|------------------|----------|--------|-----------|----------------|-----------------------|------------------|
| KRF | g/m ² | % | kN/m | kN.m/kg | kPa | kPa.m ² /g | g/m ² |
| KRF 100 | 100 | 8,0 | 1,8 | 18 | 298 | 3,0 | 50 |
| KRF 115 | 115 | 8,0 | 2,07 | 18 | 342 | 3,0 | 50 |
| KRF 135 | 135 | 8,0 | 2,43 | 18 | 402 | 3,0 | 50 |
| KRF 150 | 150 | 8,0 | 2,7 | 18 | 446 | 3,0 | 50 |
| KRF 175 | 175 | 8,0 | 3,06 | 17,5 | 518 | 3,0 | 50 |
| KRF 185 | 185 | 8,0 | 3,24 | 17,5 | 548 | 3,0 | 50 |
| KRF 200 | 200 | 8,0 | 3,51 | 17,6 | 595 | 3,0 | 50 |
| KRF 275 | 275 | 8,0 | 4,41 | 16,0 | 748 | 3,0 | 50 |

| PROPERTY | GRAMMAGE | MOISTURE | SCT CD | BURST STRENGHT | COBB60 TOP |
|---------------|----------|----------|----------|----------------|------------|
| TOLERANCES | ± 5 % | ± 1,5 | (-) 10 % | (-) 15 % | (+) 15 |
| TEST STANDARD | ISO 536 | ISO 287 | ISO 9895 | ISO 2758 | ISO 535 |

*Sampling is done according to EN ISO 186 Method. Conditioning: T= 23 ±1 °C and RH= 50 ± 3% in accordance with EN ISO 187.

**Unless otherwise stated, our product specifications are for the Top Side.

***Width Tolerance (-) 1 (+) 3 mm

****Reel Core ID: 100 (+/-) 2mm